

American Clay Earth Plaster THREE SYSTEMS Purchasing & Installation Guide

SYSTEM	PLASTER FINISH	SURFACE PREP	BASE COAT	FINISH COAT	COMPRESSION
TRADITIONAL Recommended for Do-It-Yourselfers, easiest to apply, greenest approach, best reparability. Base and finish coats are reworkable after drying.	Loma	See detailed instructions for specific substrate preparation. The entire surface must be primed with an approved paint primer* mixed with American Clay Primer Sand, or our Sanded Primer Elite. A second coat of primer sand must be applied to all outside corners. PRISA	 Covers up to 200 square feet per bag	 Covers up to 200 square feet per bag	This critical step compacts and strengthens the surface, reduces trowel marks, and prevents dusting. For additional finishing techniques, please see full instructions on our website
	Porcelina		 Covers up to 300 square feet per bag		
	Marittimo		 Covers up to 180 square feet per bag		
	Enjarre		 Covers up to 140 square feet per bag		
DOS MANOS CLASSIC Time-saving, breathable and green with most of the health benefits & reparability of Traditional. Experience with drywall or plastering tools helpful. Base and finish coats are reworkable after drying.	Loma	See detailed instructions for specific substrate preparation. The entire wall should be primed with an approved paint primer*. All outside corners MUST be primed with TWO coats of an approved paint primer* mixed with American Clay Primer Sand, or our Sanded Primer Elite. PRISA	 Covers up to 200 square feet per bag	 Covers up to 200 square feet per bag	This critical step compacts and strengthens the surface, reduces trowel marks, and prevents dusting. For additional finishing techniques, please see full instructions on our website
	Porcelina		 Covers up to 300 square feet per bag		
	Marittimo		 Covers up to 180 square feet per bag		
	Enjarre		 Covers up to 140 square feet per bag		
DOS MANOS PROFESSIONAL Greatest durability. Professional installation highly recommended. Some of the natural qualities are diminished. Base and finish coats are reworkable after drying. Repairs should be made by an experienced professional.	Loma	See detailed instructions for specific substrate preparation. The entire wall should be primed with an approved paint primer*. All outside corners MUST be primed with TWO coats of an approved paint primer* mixed with American Clay Primer Sand, or our Sanded Primer Elite. PRISA	 Covers up to 200 square feet per bag	 Covers up to 200 square feet per bag	This critical step compacts and strengthens the surface, reduces trowel marks, and prevents dusting. For additional finishing techniques, please see full instructions on our website
	Porcelina		 Covers up to 300 square feet per bag		
	Marittimo		 Covers up to 180 square feet per bag		
	Enjarre		 Covers up to 140 square feet per bag		
ENJARRE ONE COAT Affordability for large commercial projects. It also provides a unique option to homeowners or builders so that they can choose to start with a single coat of plaster and later upgrade with a second coat of one of our premier plasters. Enjarre™ can be both sprayed on or hand applied.	Enjarre	See detailed instructions for specific substrate preparation. If a BINDER is used the entire wall should be coated with an approved paint primer*. If a BINDER is NOT used the entire wall MUST be coated with an approved paint primer* mixed with American Clay's Primer Sand or our Sanded Primer Elite. All outside corners MUST have TWO coats of an approved paint primer* mixed with American Clay Primer Sand, or our Sanded Primer Elite. PRISA	 Covers up to 140 square feet per bag	 Covers up to 140 square feet per bag	This critical step compacts and strengthens the surface, reduces trowel marks, and prevents dusting. For additional finishing techniques, please see full instructions on our website.



1.866.404.1634
www.americanclay.com

PRISA = PRIMER SAND MIX WITH AN APPROVED PRIMER OR SANDED PRIMER ELITE*

= WATER

= Binder**

= LOMA

= PORCELINA

= ENJARRE

= MARITTIMO

= COLOR PACK

REVISED 07-19-2011

*Primer Sand can be an approved multipurpose, transitional or stain-blocking paint primer mixed with American Clay Primer Sand, or use American Clay Sanded Primer Elite. Lightweight and topping compounds may require a primer coat prior to the application of our Sanded Primer Elite. Test in a small area prior to proceeding on the entire project to check suitability of the required preparation. An up-to-date list is available on the web site in the "Product Application" section.

** Binder can be PlasterPlus, Up & EZ! or Mud Glue™